

### 1 IDENTIFICATION OF THE PREPARATION AND COMPANY

1. Product Name: CORROLESS CCI 400

2. Product Code: LC00400

Revision: 5.0

Issue Date: 08/01/15

Intended Use: Industrial Corrosion Inhibitor.

3. Supplier:

CORROLESS Corrosion Control

Kelvin Way, West Bromwich West Midlands

B70 7JZ, United Kingdom

Telephone: +44 (0)121 525 5665 Facsimile: +44(0)121 553 2787

( Not 24Hrs )

Email: contact@corroless.com
Website: www.corroless.com

### **2 HAZARDS IDENTIFICATION**

Flammable

Repeated exposure may cause skin dryness or cracking

Toxic to aquatic organisms: may cause long-term adverse effects in the aquatic environment

# **3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name Of Substance & [EINECS No]	Concentration	Symbol	R Phrases
Turpentine Substitute[265-191-7]	25-50 %	Xn	R10-51/53-65-66
White spirit[265-191-7]	1-10 %	Xn	R10-51/53- 65-66

#### 4 FIRST AID MEASURES

General

- \* In all cases of doubt, or when symptoms persist, seek medical attention.
- $^{\star}$  If unconscious place in recovery position, give nothing by mouth.

Inhalation

- \* Remove to fresh air.
- $\ ^{\star}$  If breathing is irregular or stopped, administer artificial respiration. Eye Contact
- $^{\star}$  Immediately irrigate copiously with clean water for at least 10 minutes. Skin Contact
  - \* Remove contaminated clothing.
  - \* Wash skin thoroughly with soap and water or recognised skin cleaner.
  - \* Do NOT use solvents or thinners.

Ingestion

- \* If swallowed obtain immediate medical attention.
- \* Keep at rest.
- \* Do NOT induce vomiting.

# **5 FIRE FIGHTING MEASURES**

- \* Extinguishing Media: foam, CO2, powder or water fog.
- \* Never use water jets or water from buckets etc. to fight fire.
- \* Closed packages may be cooled with water spray.
- \* Fire will produce dense black smoke.
- \* Exposure to decomposition products may cause a health hazard.
- \* Appropriate self contained breathing apparatus may be required.
- \* Cool closed containers exposed to fire with water.
- \* Do not allow run-off from fire-fighting to enter drains or water courses.

### **6 ACCIDENTAL RELEASE MEASURES**

- \* Exclude sources of ignition.
- \* Ventilate the area.
- \* Exclude non-essential personnel.
- \* Avoid breathing vapours.
- \* Contain/collect spillage with non-combustible absorbent materials.

#### 7 HANDLING AND STORAGE

#### Handling

- \* Vapours are heavier than air & may spread along floors.
- \* Keep the container tightly closed.
- \* Isolate from sources of heat, sparks and open flame.
- \* Avoid skin and eye contact/inhalation of vapour and mist.
- \* The Manual Handling Operation Regulations apply.
- \* Guide pack weight:[5 Ltr= 6 Kgs] [20 Ltr= 22 Kgs] [25 Ltr= 27 Kgs]

#### Storage

- \* HSE guidance note Storage of Flammable Liquids in Containers, HS(G)51 should be observed.
- \* HSE guidance note: Storage of Packaged Dangerous Substances HS(G)71 should be observed.
- \* Observe the label precautions.
- \* Separate from oxidising agents.

## **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Measures

- \* Provide adequate ventilation.
- \* If ventilation insufficient to maintain concentrations below relevant WEL's, suitable respiratory protective equipment should be worn.
- Workplace Exposure Limits (WEL's) Expressed as parts per million if available, else milligrams/cubic metre(m).
  - \* Those marked "REC" are unofficial limits provided for guidance only.

Substance	VIR	8hr TWA	15 Min STEL	Type	Skin	Notes
Turpentine Substitute	V	600.00m		WEL	N	
White spirit	V	100.000	125.000	WEL	N	
Inhalable Dusts	I	10.000		WEL	N	
Respirable Dusts	R	4.000		WEL	N	
V=Vapour, I=Inhalable dust, R=Respirable dust						

Respiratory Protection

\* If exposure cannot be controlled by ventilation/extraction, suitable respiratory protection should be worn.

Hand, Eye, Skin Protection

- \* Equipment conforming to Use of PPE Regulations should be worn.
- \* COSHH Regulations apply.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

a) Physical State : Semi fluid grease
b) Flash Point : Between 32 & 55°C

c) Specific Gravity :  $0.89 \pm 0.05$ 

d) Vapour Density : Heavier Than Air.

e) Solubility in Water : Immiscible with Water

# **10 STABILITY AND REACTIVITY**

- \* Stable under recommended storage and handling conditions.
- \* Decomposition products are carbon monoxide, carbon dioxide, smoke and oxides of nitrogen.
- \* Keep away from oxidising agents, alkali and acid.

# 11 TOXICOLOGICAL INFORMATION

- \* No data available on product itself, however: -
- \* Exposure to organic solvent vapours may result in adverse health effects on mucous membrane, respiratory system ,renal and central nervous systems. Symptoms include headaches, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
- \* Repeated or prolonged contact may result in non-allergic contact dermatitis and absorption through the skin.

# **12 ECOLOGICAL INFORMATION**

- \* Air Pollution Control or Integrated Pollution Control regulations made under the Environmental Protection Act may apply.
- \* Do not allow to enter drains or water courses.
- \* This product contains a substance which is :- R51 Toxic to aquatic organisms.

#### 13 DISPOSAL CONSIDERATIONS

\* In accordance with Control of Pollution Act and Environmental Protection Act.

### 14 TRANSPORT INFORMATION

	CDG- CPL	ADR	IMDG			
Class Number	3	3	3			
Subsidiary Hazard Code	NUL	NUL	NUL			
Packing Group	III	Ш	III			
Tunnel Codes / EmS Codes		(D/E)	F-E;S-E			
Proper Shipping Name	Paint related material (White Spirit)					
U.N. Number	1263					
Marine Pollutant : Yes						

### 15 REGULATORY INFORMATION

\* Classified and labelled for supply in accordance with the Chemicals (Hazard Information and Packaging) Regulations as follows:-

**HEALTH** Xn Harmful

PHYSICO-CHEMICAL F- Flammable

**ENVIRONMENT** N Dangerous for the Environment



R10 Flammable

R66 Repeated exposure may cause skin dryness or cracking

R51/53Toxic to aquatic organisms: may cause long-term adverse effects in the aquatic environment

S23a Do not breathe vapour

S43b In case of fire, use foam, CO2, powder or water fog

S51 Use only in well ventilated areas

S7/9 Keep container tightly closed and in a well ventilated place

# **16 OTHER INFORMATION**

\* Do not use for purposes other than those shown in Section 1 without referring to the supplier.

<sup>\*</sup> The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by health and safety legislation.