

1 IDENTIFICATION OF THE PREPARATION AND COMPANY

1. Product Name: CORROLOSS EPF TEMPERATE HARDENER (Black)
 Product Code: 4056103
 Revision: 7.00
 Issue Date: 08/01/15
2. Intended Use: Hardener for 2 Component paint system
 to be mixed 1:1 with 2916RHG Base

3. Supplier:

CORROLESS Corrosion Control
 Kelvin Way,
 West Bromwich
 West Midlands
 B70 7JZ, United Kingdom
 Telephone: +44 (0)121 525 5665
 Facsimile: +44(0)121 553 2787
 (Not 24Hrs)
 Email: contact@corroless.com
 Website: www.corroless.com

2 HAZARDS IDENTIFICATION

Harmful: Danger of serious damage to health by prolonged exposure through inhalation.
 May cause sensitisation by skin contact
 Irritating to the eyes and skin

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name Of Substance & [EINECS No]	Concentration	Symbol	R Phrases
Xylene, mixture of isomers[215-535-7]	1-10 %	Xn	R10-20/21-38
2,4,6- Tris(dimethylaminomethyl)phenol[202-013-9]	1-10 %	Xn	R22-36/38
Alkylated phenolic polyamine	25-50 %	Xi	R36/38-43
Crystalline silica.[238-878-4]	25-50 %	Xn	R48/20

4 FIRST AID MEASURES

General

- * In all cases of doubt, or when symptoms persist, seek medical attention.
- * If unconscious place in recovery position, give nothing by mouth.

Inhalation

- * Remove to fresh air.
- * If breathing is irregular or stopped, administer artificial respiration.

Eye Contact

- * Immediately irrigate copiously with clean water for at least 10 minutes.

Skin Contact

- * Remove contaminated clothing.
- * Wash skin thoroughly with soap and water or recognised skin cleaner.
- * Do NOT use solvents or thinners.

Ingestion

- * If swallowed obtain immediate medical attention.
- * Keep at rest.
- * Do NOT induce vomiting.

5 FIRE FIGHTING MEASURES

- * Extinguishing Media: alcohol resistant foam, CO2, powder or water fog.
- * Never use water jets or water from buckets etc. to fight fire.
- * Closed packages may be cooled with water spray.
- * Fire will produce dense black smoke.
- * Exposure to decomposition products may cause a health hazard.
- * Appropriate self contained breathing apparatus may be required.
- * Cool closed containers exposed to fire with water.
- * Do not allow run-off from fire-fighting to enter drains or water courses.

6 ACCIDENTAL RELEASE MEASURES

- * Exclude sources of ignition.
- * Ventilate the area.
- * Exclude non-essential personnel.
- * Avoid breathing vapours.
- * Contain/collect spillage with non-combustible absorbent materials.

7 HANDLING AND STORAGE

Handling

- * Persons with history of skin sensitisation problems should NOT be employed where this product is used unless under appropriate medical supervision.
- * Vapours are heavier than air & may spread along floors.
- * Keep the container tightly closed.
- * Isolate from sources of heat, sparks and open flame.
- * Avoid skin and eye contact/inhalation of vapour and mist.
- * The Manual Handling Operation Regulations apply.
- * Guide pack weight: [5 Ltr= 9 Kgs] [20 Ltr= 32 Kgs] [25 Ltr= 39 Kgs]

Storage

- * HSE guidance note: Storage of Packaged Dangerous Substances HS(G)71 should be observed.
- * Observe the label precautions.
- * Separate from oxidising agents.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- * Persons with a history of skin sensitisation problems should be employed in processes in which this product is used only under appropriate medical supervision.

Engineering Measures

- * Provide adequate ventilation.
- * Spray in booths/enclosures with sufficient ventilation to prevent mist escaping to surrounding area.
- * Respiratory protective equipment should be worn by spray booth operators.

Workplace Exposure Limits (WEL's) - Expressed as parts per million if available, else milligrams/cubic metre(m).

- * Those marked "REC" are unofficial limits provided for guidance only.

Substance	VIR	8hr TWA	15 Min STEL	Type	Skin	Notes
Xylene, mixture of isomers	V	50.000	100.000	WEL	Y	BMGV
Crystalline silica.	R	0.10m		WEL	N	as dust
Inhalable Dusts	I	10.000		WEL	N	
Respirable Dusts	R	4.000		WEL	N	

V=Vapour, I=Inhalable dust, R=Respirable dust

Respiratory Protection

- * Air fed respiratory protection should be worn when product sprayed and exposure of the sprayer cannot be controlled below WEL.

Hand, Eye, Skin Protection

- * Equipment conforming to Use of PPE Regulations should be worn.
- * COSHH Regulations apply.

9 PHYSICAL AND CHEMICAL PROPERTIES

- a) Physical State : Liquid
- b) Flash Point : Above 55°C
- c) Specific Gravity : 1.40 ± 0.1
- d) Vapour Density : Heavier Than Air.
- e) Solubility in Water : Immiscible with Water

10 STABILITY AND REACTIVITY

- * Stable under recommended storage and handling conditions.
- * Decomposition products are carbon monoxide , carbon dioxide, smoke and oxides of nitrogen.
- * Keep away from oxidising agents, alkali and acid.

11 TOXICOLOGICAL INFORMATION

- * No data available on product itself, however: -
- * COSHH requires that persons exposed to respiratory sensitisers, are subject to appropriate health surveillance.
- * Substances used within this product have irritant properties.
- * Prolonged or repeated contact with skin/mucous membrane may result in symptoms such as redness, blistering or dermatitis.
- * Splashes in eyes may cause irritation.
- * Inhalation of droplets/aerosols may irritate respiratory tract.
- * Ingestion may lead to severe respiratory difficulties, stimulation of central nervous system and in extreme cases unconsciousness.
- * Cases of allergic skin reaction have been observed.
- * Repeated or prolonged contact may result in non-allergic contact dermatitis and absorption through the skin.

12 ECOLOGICAL INFORMATION

- * Air Pollution Control or Integrated Pollution Control regulations made under the Environmental Protection Act may apply.
- * Do not allow to enter drains or water courses.

13 DISPOSAL CONSIDERATIONS




- * In accordance with Control of Pollution Act and Environmental Protection Act.

14 TRANSPORT INFORMATION

	CDG- CPL	ADR	IMDG
Class Number	NUL	NUL	NUL
Subsidiary Hazard Code	NUL	NUL	NUL
Packing Group	NUL	NUL	NUL
Tunnel Codes / EmS Codes			
Proper Shipping Name	Not Classified		
U.N. Number	Not Classified		
Marine Pollutant : No			

15 REGULATORY INFORMATION

* Classified and labelled for supply in accordance with the Chemicals (Hazard Information and Packaging) Regulations as follows:-

HEALTH	Xn,XiHarmful & Irritant	
PHYSICO-CHEMICAL	Not Classified	
ENVIRONMENT	Not Classified	

R48/20Harmful:danger of serious damage to health by prolonged exposure through inhalation

R43 May cause sensitisation by skin contact

R36/38Irritating to the eyes and skin

S23c Do not breathe vapour or spray mist

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S42 During spraying wear suitable respiratory equipment

S7/9 Keep container tightly closed and in a well ventilated place

S24 Avoid contact with skin

* The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by health and safety legislation.

16 OTHER INFORMATION

* Do not use for purposes other than those shown in Section 1 without referring to the supplier.