

## 1 IDENTIFICATION OF THE PREPARATION AND COMPANY

1. Product Name: Corroless QDR3 (Black)

Product Code: LQDR003

Revision: 3.00
Issue Date: 08/01/15

2. Intended Use: Industrial Primer

3. Supplier:

CORROLESS Corrosion Control

Kelvin Way, West Bromwich West Midlands

B70 7JZ, United Kingdom

Telephone: +44 (0)121 525 5665 Facsimile: +44(0)121 553 2787

(Not 24Hrs)

Email: contact@corroless.com
Website: www.corroless.com

### 2 HAZARDS IDENTIFICATION

Highly Flammable

Harmful by inhalation and contact with skin

Irritating to the skin

## **3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name Of Substance & [EINECS No]	Concentration	Symbol	R Phrases
Xylene, mixture of isomers[215-535-7]	25-50 %	Xn	R10-20/21-38
Ethyl benzene[202-849- 4]	1-10 %	Xn	R11-20
Propan-2-ol[200- 661-7]	1-10 %	Xi	R11-36-67
Silicate extenders[310-127-6]	1-10 %		

### **4 FIRST AID MEASURES**

General

- \* In all cases of doubt, or when symptoms persist, seek medical attention.
- \* If unconscious place in recovery position, give nothing by mouth.

Inhalation

- \* Remove to fresh air.
- \* If breathing is irregular or stopped, administer artificial respiration. Eye Contact
- $^{\star}$  Immediately irrigate copiously with clean water for at least 10 minutes. Skin Contact
  - \* Remove contaminated clothing.
  - \* Wash skin thoroughly with soap and water or recognised skin cleaner.
  - \* Do NOT use solvents or thinners.

Ingestion

- \* If swallowed obtain immediate medical attention.
- \* Keep at rest.
- \* Do NOT induce vomiting.

### **5 FIRE FIGHTING MEASURES**

- \* Extinguishing Media: alcohol resistant foam, CO2, powder or water fog.
- \* Never use water jets or water from buckets etc. to fight fire.
- \* Closed packages may be cooled with water spray.
- \* Fire will produce dense black smoke.
- \* Exposure to decomposition products may cause a health hazard.
- \* Appropriate self contained breathing apparatus may be required.
- \* Cool closed containers exposed to fire with water.
- $^{\star}$  Do not allow run-off from fire-fighting to enter drains or water courses.

### **6 ACCIDENTAL RELEASE MEASURES**

- \* Exclude sources of ignition.
- \* Ventilate the area.
- \* Exclude non-essential personnel.
- \* Avoid breathing vapours.
- \* Contain/collect spillage with non-combustible absorbent materials.

# **7 HANDLING AND STORAGE**

Handling

- \* Vapours are heavier than air & may spread along floors.
- \* Keep the container tightly closed.
- \* Isolate from sources of heat, sparks and open flame.
- \* Avoid skin and eye contact/inhalation of vapour and mist.
- \* The Manual Handling Operation Regulations apply.
- \* Guide pack weight:[5 Ltr= 8 Kgs] [20 Ltr= 29 Kgs] [25 Ltr= 36 Kgs]

### Storage

- \* HSE guidance note: Storage of Packaged Dangerous Substances HS(G)71 should be observed.
- \* Observe the label precautions.
- \* The accumulation of contaminated rags and of dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.
- \* Separate from oxidising agents.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures

- \* Provide adequate ventilation.
- \* If ventilation insufficient to maintain concentrations below relevant WEL's, suitable respiratory protective equipment should be worn.

Workplace Exposure Limits (WEL's) - Expressed as parts per million if available, else milligrams/cubic metre(m).

\* Those marked "REC" are unofficial limits provided for guidance only.

Substance	VIR	8hr TWA	15 Min STEL	Туре	Skin	Notes	
Xylene, mixture of isomers	V	50.000	100.000	WEL	Υ	BMGV	
Ethyl benzene	V	100.000	125.000	WEL	Υ	IOELV	
Propan-2- ol	V	400.000	500.000	WEL	N		
Silicate extenders	V	2.00m		WEL	N	as dust	
Inhalable Dusts	I	10.000		WEL	N		
Respirable Dusts	R	4.000		WEL	N		
V=Vapour, I=Inhalable dust, R=Respirable dust							

Respiratory Protection

\* Air fed respiratory protection should be worn when product sprayed and exposure of the sprayer cannot be controlled below WEL.

Hand, Eye, Skin Protection

- \* Equipment conforming to Use of PPE Regulations should be worn.
- \* COSHH Regulations apply.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

a) Physical State : Liquid

b) Flash Point
 c) Specific Gravity
 d) Vapour Density
 Less Than 21°C
 1.27 ± 0.1
 Heavier Than Air.

e) Solubility in Water : Immiscible with Water

#### 10 STABILITY AND REACTIVITY

- \* Stable under recommended storage and handling conditions.
- \* Decomposition products are carbon monoxide , carbon dioxide, smoke and oxides of nitrogen.
- \* Keep away from oxidising agents, alkali and acid.

## 11 TOXICOLOGICAL INFORMATION

- \* No data available on product itself, however: -
- \* Exposure to organic solvent vapours may result in adverse health effects on mucous membrane, respiratory system ,renal and central nervous systems. Symptoms include headaches, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
- \* Substances used within this product have irritant properties.
- \* Prolonged or repeated contact with skin/mucous membrane may result in symptoms such as redness, blistering or dermatitis.
- \* Splashes in eyes may cause irritation.
- \* Inhalation of droplets/aerosols may irritate respiratory tract.
- \* Ingestion may lead to severe respiratory difficulties, stimulation of central nervous system and in extreme cases unconsciousness.
- \* Repeated or prolonged contact may result in non-allergic contact dermatitis and absorption through the skin.

## 12 ECOLOGICAL INFORMATION

- \* Air Pollution Control or Integrated Pollution Control regulations made under the Environmental Protection Act may apply.
- \* Do not allow to enter drains or water courses.

### 13 DISPOSAL CONSIDERATIONS

\* In accordance with Control of Pollution Act and Environmental Protection Act.

## 14 TRANSPORT INFORMATION

	CDG- CPL	ADR	IMDG
Class Number	3	3	3
Subsidiary Hazard Code	NUL	NUL	NUL
Packing Group	II	II	II
Tunnel Codes / EmS Codes		(D/E)	F-E;S-E
Proper Shipping Name	Paint		
U.N. Number	1	263	
Marine Poll	utant : No		

### 15 REGULATORY INFORMATION

\* Classified and labelled for supply in accordance with the Chemicals (Hazard Information and Packaging) Regulations as follows:-

**HEALTH** Xn,Xi Harmful & Irritant

t X

PHYSICO-CHEMICAL F Highly Flammable

HISHLY P. GENEVAL

**ENVIRONMENT** 

**Not Classified** 

R11 Highly Flammable

R20/21Harmful by inhalation and contact with skin

R38 Irritating to the skin

S23c Do not breathe vapour or spray mist

S16 Keep away from sources of ignition - No Smoking

S29 Do not empty into drains

S36/37Wear suitable protective clothing and gloves

S42 During spraying wear suitable respiratory equipment

\* The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by health and safety legislation.

## **16 OTHER INFORMATION**

\* Do not use for purposes other than those shown in Section 1 without referring to the supplier.