

1 IDENTIFICATION OF THE PREPARATION AND COMPANY

- 1. Product Name: Corroless RF16 Top Coat**
 Product Code: 2004/-
 Revision: 4.00
 Issue Date: 08/01/15
- 2. Intended Use: Industrial Paint (Top Coat)
- 3. **Supplier:**
CORROLESS Corrosion Control
 Kelvin Way,
 West Bromwich
 West Midlands
 B70 7JZ, United Kingdom
 Telephone: +44 (0)121 525 5665
 Facsimile: +44(0)121 553 2787
 (Not 24Hrs)
 Email: contact@corroless.com
 Website: www.corroless.com

2 HAZARDS IDENTIFICATION

Flammable
 Harmful by inhalation and contact with skin
 Repeated exposure may cause skin dryness or cracking
 Contains Ethyl methyl ketoxime May produce an allergic reaction.
 Toxic to aquatic organisms: may cause long-term adverse effects in the aquatic environment

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name Of Substance & [EINECS No]	Concentration	Symbol	R Phrases
Xylene, mixture of isomers[215-535-7]	10-25 %	Xn	R10-20/21-38
Ethyl benzene[202-849- 4]	1-10 %	Xn	R10-20
Naptha(petroleum)hydrodesulfuized heavy[265-185-4]	25-50 %	Xn	R10-51/53-65-66-67

4 FIRST AID MEASURES

- General
- * In all cases of doubt, or when symptoms persist, seek medical attention.
 - * If unconscious place in recovery position,give nothing by mouth.
- Inhalation
- * Remove to fresh air.
 - * If breathing is irregular or stopped, administer artificial respiration.
- Eye Contact
- * Immediately irrigate copiously with clean water for at least 10 minutes.
- Skin Contact
- * Remove contaminated clothing.
 - * Wash skin thoroughly with soap and water or recognised skin cleaner.
 - * Do NOT use solvents or thinners.
- Ingestion
- * If swallowed obtain immediate medical attention.
 - * Keep at rest.
 - * Do NOT induce vomiting.

5 FIRE FIGHTING MEASURES

- * Extinguishing Media: foam, CO₂, powder or water fog.
- * Never use water jets or water from buckets etc. to fight fire.
- * Closed packages may be cooled with water spray.
- * Fire will produce dense black smoke.
- * Exposure to decomposition products may cause a health hazard.
- * Appropriate self contained breathing apparatus may be required.
- * Cool closed containers exposed to fire with water.
- * Do not allow run-off from fire-fighting to enter drains or water courses.

6 ACCIDENTAL RELEASE MEASURES

- * Exclude sources of ignition.
- * Ventilate the area.
- * Exclude non-essential personnel.
- * Avoid breathing vapours.
- * Contain/collect spillage with non-combustible absorbent materials.

7 HANDLING AND STORAGE

Handling

- * Vapours are heavier than air & may spread along floors.
- * Keep the container tightly closed.
- * Isolate from sources of heat, sparks and open flame.
- * Avoid skin and eye contact/inhalation of vapour and mist.
- * The Manual Handling Operation Regulations apply.
- * Guide pack weight: [5 Ltr= 7 Kgs] [20 Ltr= 25 Kgs] [25 Ltr= 31 Kgs]

Storage

- * Dangerous Substances & Explosive Atmospheres Regs apply.
- * HSE guidance note: Storage of Packaged Dangerous Substances HS(G)71 should be observed.
- * Observe the label precautions.
- * The accumulation of contaminated rags and of dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.
- * Separate from oxidising agents.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures

- * Provide adequate ventilation.
- * If ventilation insufficient to maintain concentrations below relevant WEL's, suitable respiratory protective equipment should be worn.

Workplace Exposure Limits (WEL's) - Expressed as parts per million if available, else milligrams/cubic metre (m).

- * Those marked "REC" are unofficial limits provided for guidance only.

Substance	VIR	8hr TWA	15 Min STEL	Type	Skin	Notes
Xylene, mixture of isomers	V	50.000	100.000	WEL	Y	BMGV
Ethyl benzene	V	100.000	125.000	WEL	Y	IOELV
Inhalable Dusts	I	10.000		WEL	N	
Respirable Dusts	R	4.000		WEL	N	

V=Vapour, I=Inhalable dust, R=Respirable dust

Respiratory Protection

- * Air fed respiratory protection should be worn when product sprayed and exposure of the sprayer cannot be controlled below WEL.

Hand, Eye, Skin Protection

- * Equipment conforming to Use of PPE Regulations should be worn.
- * COSHH Regulations apply.

9 PHYSICAL AND CHEMICAL PROPERTIES

- a) Physical State : Liquid
- b) Flash Point : Between 21 & 32°C
- c) Specific Gravity : 1.06 ± 0.1
- d) Vapour Density : Heavier Than Air.
- e) Solubility in Water : Immiscible with Water

10 STABILITY AND REACTIVITY

- * Stable under recommended storage and handling conditions.
- * Decomposition products are carbon monoxide , carbon dioxide, smoke and oxides of nitrogen.
- * Keep away from oxidising agents, alkali and acid.

11 TOXICOLOGICAL INFORMATION

- * No data available on product itself, however: -
- * Exposure to organic solvent vapours may result in adverse health effects on mucous membrane, respiratory system ,renal and central nervous systems. Symptoms include headaches, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
- * Repeated or prolonged contact may result in non-allergic contact dermatitis and absorption through the skin.

12 ECOLOGICAL INFORMATION

- * Air Pollution Control or Integrated Pollution Control regulations made under the Environmental Protection Act may apply.
- * Do not allow to enter drains or water courses.
- * This product contains a substance which is :-
R51 - Toxic to aquatic organisms.

13 DISPOSAL CONSIDERATIONS




- * In accordance with Control of Pollution Act and Environmental Protection Act.

14 TRANSPORT INFORMATION

	CDG- CPL	ADR	IMDG
Class Number	3	3	3
Subsidiary Hazard Code	NUL	NUL	NUL
Packing Group	III	III	III
Tunnel Codes / EmS Codes		(D/E)	F-E;S-E
Proper Shipping Name	Paint (Solvent Naphtha)		
U.N. Number	1263		
Marine Pollutant : Yes			

15 REGULATORY INFORMATION

* Classified and labelled for supply in accordance with the Chemicals (Hazard Information and Packaging) Regulations as follows:-

HEALTH	Xn	Harmful	
PHYSICO-CHEMICAL	F-	Flammable	
ENVIRONMENT	N	Dangerous for the Environment	

R10 Flammable

R20/21 Harmful by inhalation and contact with skin

R66 Repeated exposure may cause skin dryness or cracking

P99% Contains Ethyl methyl ketoxime May produce an allergic reaction.

R51/53 Toxic to aquatic organisms: may cause long-term adverse effects in the aquatic environment

S23c Do not breathe vapour or spray mist

S33 Take precautionary measures against static discharges

S36 Wear suitable protective clothing

S42 During spraying wear suitable respiratory equipment

S43b In case of fire, use foam, CO₂, powder or water fog

* The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by health and safety legislation.

16 OTHER INFORMATION

* Do not use for purposes other than those shown in Section 1 without referring to the supplier.